

			C1200	C1500	C1600
ENGINE					
Liquid-cooled twin cylinder	Kubota D1105 STAGE V - TIER 4	Diesel 24,8 hp	✓	—	—
Liquid-cooled twin cylinder	Kubota D1305 STAGE V - TIER 4	Diesel 24,8 hp	—	✓	✓
TRANSMISSION					
Type	Hydrostatic		✓	✓	✓
Hydraulic pump	2 variable piston pumps 83.2 lt/min 365bar (21.9 gpm 5230 psi)		✓	—	—
	2 variable piston pumps 93 lt/min 365bar (24.6 gpm 5234 psi)		—	✓	✓
TRACKS					
Crawler width	200 mm (7.9 in)		✓	—	—
	230 mm (9.1 in)		—	✓	✓
Track roller with grease	5		✓	✓	✓
HYDRAULIC SYSTEM SPEC 1 - 2					
Hydraulic pump	Gear pump		✓	✓	✓
Flow std	1x26/min (1x 6.86 gpm)		✓	—	—
	1x27 l/min (1x7.1 gpm)		—	✓	✓
Maximum pressure	200 bar (2901 psi)		✓	✓	✓
HYDRAULIC SYSTEM WITH HI FLOW SPEC 3					
Hydraulic pump	Variable pistons pumps		✓	✓	✓
Flow std	2x27=54 l (2x 7.1= 14.2 gpm)		✓	—	—
	2x29=58 l (1x 7.7= 15.4 gpm)		—	✓	✓
Maximum pressure	280 bar (4061 psi)		✓	✓	✓
HYDRAULIC SYSTEM SPEC 2 (Only U.S.A.)					
Flow std	1x36,3 lt (1x9.6 gpm)		✓	—	—
	1x39,7 lt (1x10.5 gpm)		—	✓	✓
Maximum pressure	180 bar (2611 psi)		✓	✓	✓
HYDRAULIC SYSTEM WITH HI FLOW SPEC 3 (Only U.S.A.)					
Hi-Flow	2x27=54 lt (2x 7= 14 gpm)		✓	—	—
	2x29=58 lt (1x 7.67= 15.34 gpm)		—	✓	✓
Maximum pressure	280 bar (4061 psi)		✓	✓	✓
ADDITIONAL HYD OUTPUT					
Spec-1	n° 2		✓	✓	✓
Spec-2	n° 5		✓	✓	✓
Spec-3	n° 5		✓	✓	✓
PERFORMANCE AND DIMENSIONS					
Max. Travel Speed	6,9 Km/h (4.3 mph)		✓	—	—
	7,6 Km/h (4.7 mph)		—	✓	✓
Dry Weight	795 Kg (1753 lb)		✓	—	—
	910 Kg (2006 lb)		—	✓	—
	919 kg (2027 lb)		—	—	✓
Parking brake	Yes		✓	✓	✓
Cruise control	Yes		✓	✓	✓
Vessel capacity	da 0,39 a 0,67 m ³ (from 0.51 to 0.88 yd ³)		✓	✓	✓